

PRODUCT FOCUS

Patented Air Gap
US Patent #
6,204,602



HIGHMAX 55W (SPIRAL)
3,500 Lumens
(250 Watt Replacement)



HIGHMAX 65W (QUADRUPLE)
4,200 Lumens
(300 Watt Replacement)



HIGHMAX 85W (QUADRUPLE)
5,500 Lumens
(400 Watt Replacement)



HIGHMAX 105W (QUADRUPLE)
6,900 Lumens
(500 Watt Replacement)

120V/277V
Available



Applications:

- HighBays
- LowBays
- Gymnasiums
- Shop Floors
- Warehouses
- Churches
- Schools

Benefits:

- Patented Air-Gap guarantees long life – lasts 10,000 hours
- High Lumens using less energy
- Self Ballasted
- Instant-on, flicker-free electronics
- CRI 85
- Available in Edison Base/Mogul Base
- Available in 2700K and 5000K

MaxLite™
19 Chapin Road,
Building B
Pine Brook, NJ 07058-2005
www.maxlite.com
Tel: (973) 244-7300
Fax: (973) 244-7333
E-mail: info@maxlite.com

ISO 9002 Certified

HIGHMAXSPECIFICATIONS

Watts	Order Code	Description	Lumens (Lm)	Efficacy (LM/W)	Lamp Life (Hrs)	Color / CRI* (°K) / (Ra)	Operating Temp. (°F)	Pack	Dimensions (w"x h")
55	35801	SKS55EA Spiral 120V	3,500	63.6	10,000	2700 / 85	0-160	12	3.5 x 10
55	35802	SKS55EA50 Spiral 5000K 120V				5000 / 85			
55	35803	SKS55EA250 Spiral 5000K 277V				5000 / 85			
65	35811	SKQ65EA Quad 120V	4,200	64.6	10,000	2700 / 85	0-160	12	3.5 x 11
65	35812	SKQ65EA50 Quad 5000K 120V				5000 / 85			
65	35813	SKQ65EA250 Quad 5000K 277V				5000 / 85			
85	35821	SKQ85EA Quad 120V	5,500	64.7	10,000	2700 / 85	0-160	12	3.5 x 13
85	35822	SKQ85EA50 Quad 5000K 120V				5000 / 85			
85	35823	SKQ85EA250 Quad 5000K 277V				5000 / 85			
105	35831	SKQ105EA Quad 120V	6,900	65.7	10,000	2700 / 85	0-160	12	3.5 x 15
105	35832	SKQ105EA50 Quad 5000K 120V				5000 / 85			
105	35833	SKQ105EA250 Quad 5000K 277V				5000 / 85			

*CRI = Color Rendering Index

Notes: (1) Not suitable for dimming circuits or timing devices. (2) Use in recessed or enclosed lighting fixtures with elevated line voltage may shorten life.